



## Extraction of positive and negative ion beams by discrete and modal focusing effects

Stamate, Eugen

*Publication date:*  
2010

[Link back to DTU Orbit](#)

*Citation (APA):*

Stamate, E. (2010). *Extraction of positive and negative ion beams by discrete and modal focusing effects*. Abstract from 63rd Annual Gaseous Electronics Conference and 7th International Conference on Reactive Plasmas, Paris, France.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Abstract Submitted  
for the GEC10 Meeting of  
The American Physical Society

Sorting Category: 2.2 (E)

**Extraction of positive and negative ion beams by discrete and modal focusing effects** EUGEN STAMATE, Technical University of Denmark — Positive or negative ion beams extracted from plasma are used in a large variety of surface functionalization techniques such as implantation, etching, surface activation, passivation or oxidation. Of particular importance is the surface treatment of materials sensitive to direct plasma exposure due to high heat fluxes, the controllability of the ion incidence angle, and charge accumulation when treating insulating materials. Despite of a large variety of plasma sources available for ion beam extraction, there is a clear need for new extraction mechanisms that can make available ion beams with high current densities that can treat surfaces placed adjacent to the extraction region. This work introduces a new phenomenology for ion beam extraction using the discrete and modal focusing effects associated with three-dimensional plasma-sheath-lenses. Three-dimensional simulations are used to explain the plasma sheath lens design and the extraction mechanism. Experiments are performed in a matrix-ECR plasma source with transversal magnetic filter for electron temperature control. The discharge is operated at pressures below 1 mTorr and low plasma densities for a density ratio of negative ions to electrons larger than 300. The focused ion beams of positive or negative ions are used to induce surface modification on conductive and insulating substrates.

☒ Prefer Oral Session  
☐ Prefer Poster Session

Eugen Stamate  
eust@risoe.dtu.dk  
Risoe DTU, Technical University of Denmark

Date submitted: 13 Jun 2010

Electronic form version 1.4